

— **Size doesn't matter –
it's performance that counts.**

The compact mini cordless drill Available in C-shape or T-shape



FESTOOL

Tools for the toughest demands

A perfect fit in the hand: These extra-small sizes will impress you with their compact shape, light weight, slimline grip and optimum weight distribution. And they can be put down safely at any time.



Strong arguments: 10.8 volts and optimum power with 12-stage torque adjustment and control as well as long-lasting lithium-ion battery packs.



Versatile courtesy of the FastFix drill chuck with 10 mm clamping range, angle attachment and CENTROTEC quick-change system. All bits can also be inserted into the direct fitting.



Easily reach every screw: Use the angle attachment for tight corners and integrated LED light for dark spaces.



Practical: Bit storage for 4 bits, right-handed and left-handed belt clip and battery pack with capacity indicator.



Li-Ion



Small dimensions. Great performance. The compact mini cordless drill

Light and still amazingly strong. And now available in the classic T-shape. These compact mini drill/drivers are impressive on account of their exceptional torque which works powerfully, even in hard-to-reach spaces. The extremely compact construction and even weight distribution make it ideal for working overhead. And its long-lasting lithium-ion battery packs with charge status indicator, CENTROTEC quick-change system and SERVICE all-inclusive package make it perfect for professional use.



SERVICE
all-inclusive



Top service performance: The Festool limited 3 year warranty covers defects in materials and workmanship on the pre-condition that the tool is used and operated in compliance with the Festool operating instructions. For exclusions see www.festool.com.au



Technical specifications, scope of delivery and accessories



Technical specifications **TXS | CXS**

Battery voltage	10.8 V
Idle engine speed (1st/2nd) gear	0–430/0–1,300 min ⁻¹
Drilling diameter, wood/steel	12/8 mm
Torque adjustment (1st/2nd) gear	0.3–3.4 Nm
Max. torque (wood/steel)	10/16 Nm
Chuck range	1–10 mm
Li-Ion battery capacity	2.6 Ah
Charging time Li Ion (2.6 Ah)	45 min
Weight with Li Ion	0.9 kg

Scope of delivery **TXS Li 2.6**

TXS Li 2.6 Plus

Charger MXC, 2nd battery pack 2.6 Ah, FastFix drill chuck 10 mm, CENTROTEC tool chuck, CENTROTEC bit holder, in a SYSTAINER SYS 1 T-LOC


Order no.

Not available

TXS Li 2.6 Set

Charger MXC, 2nd battery pack 2.6 Ah, FastFix drill chuck 10 mm, CENTROTEC tool chuck, CENTROTEC bit holder, bit PZ 2, FastFix angle attachment, in a SYSTAINER SYS 1 T-LOC

564516



Scope of delivery **CXS Li 2.6**

Order no.

CXS Li 2.6 Plus

Not available

Charger MXC, 2nd battery pack 2.6 Ah, FastFix drill chuck 10 mm, CENTROTEC tool chuck, CENTROTEC bit holder, in a SYSTAINER SYS 1 T-LOC

CXS Li 2.6 Set

564540

Charger MXC, 2nd battery pack 2.6 Ah, FastFix drill chuck 10 mm, CENTROTEC tool chuck, CENTROTEC bit holder, bit PZ 2, FastFix angle attachment, in a SYSTAINER SYS 1 T-LOC

Accessories **TXS | CXS**

Order no.

- | | | |
|---|---|---------------|
| 1 | Angle attachment XS-AS | 497951 |
| 2 | Drill chuck BF-FX 10 | 499949 |
| 3 | Battery pack BP-XS 2.6 Ah Li Ion
suitable for TXS, CXS Facelift
and all existing CXS models | 500184 |
| 4 | Rapid charger MXC
suitable for the battery packs
BP-XS 2.6 Ah Li Ion and previous
CXS battery sticks BP-XS 1.5 Ah | 497498 |



▲ The CENTROTEC system replaces drill chuck and bit holder for quick application changes.

▶ Ideal if you're in a tight spot: All bits can also be inserted into the direct fitting.





The Festool 3 year warranty covers defects in materials & workmanship on the pre-condition that the tool is used in compliance with operating instructions. Details at www.festool.com.au



Take-back of old devices, recycling, waste avoidance. For a clean environment. For more information, go to www.festool.com

Retailer

Festool CXS

Valid from 2015

Order no. 64432 AUS/en



4 014549 242179

Vibration levels and emission values can be found in the operating instructions at www.festool.com/vibration

Subject to changes and errors. All images are non-binding.

Produced for Festool GmbH, 73240 Wendlingen, 11/2014

FESTOOL

Tools for the toughest demands

Festool Australia

Postal address: PO Box 4401

Dandenong South VIC 3164

Australia

Service Hotline: 1300 063 900

Fax: 03 8795 9221

E-mail: customercare@tooltechnic.com.au

Hindin Marquip Ltd.

1012 Great South Road

1061 Penrose – Auckland

Phone +64 9 9131666

E-mail hamish@hml.co.nz

www.festool.com.au