

When we talk about cutting the  
**perfect edge**, we mean just that.

And a perfect edge starts with the CONTURO KA 65.



**FESTOOL**

Tools for the toughest demands



**Perfect ergonomics:** Clear view of the workpiece, machine housing does not heat up, edging height adjusted in a single turn.



**Clean cartridge gluing system:** The glue comes in cartridge form and is easy to insert. The heating grid only melts the exact amount of glue required, thereby retaining the adhesive properties and colour of the glue to ensure perfect results.



**Practical display:** Indicates how many metres of edging can be processed at the preset edging height and glue quantity.



**Stationary application for greater versatility:** Affixing edging to mitred surfaces ( $0^{\circ}$  -  $47^{\circ}$ ) is also possible with the CONTURO, simply by inserting an adapter plate in the work bench.



**Systems get it done:** With additional roller for narrow curves or rigid edging material, plus holder for long strips of edging. The trimming machine is ideal for precision trimming, while the scraper is perfect for smoothing edges.



## Perfect edge in a system.



### MFK 700 EQ/Basic Items included

Order no.

#### Module edge router MFK 700 EQ/Basic-Plus 230-240V

574457

Ball bearing guide brake, in a Systainer 2 T-Loc

Ideal for routing mitred edges: the plane cutter S8 HW OFK. Classic ogee cutters with reversible blades with 1, 1.5, 2 and 3 mm radius are suitable for milling curves. >>> Accessory orders at [www.festool.com.au](http://www.festool.com.au)

### VAC SYS Items included

Order no.

#### VAC SYS Set SE 1

712220

Vacuum pump VAC SYS VP, vacuum clamping unit VAC SYS SE 1, vacuum pad VAC SYS VT D 125, foot valve, vacuum hose

### Order now:

The book for the perfect edge.  
[www.festool.com.au](http://www.festool.com.au)

Platzhalter  
CONTURO-Buch  
Titelseite



▲ Developed for routing edging: the MFK 700 Basic edge router with spring-loaded ball bearing guide brake for machining the most delicate of edging without leaving marks.

► For the simple attachment of edging to round workpieces: workpiece is accessible from all sides with the VAC SYS vacuum clamping system.





## Edge bander **CONTURO KA 65**



### **CONTURO** Technical data

|  |               |            |
|--|---------------|------------|
| Power  | 1,200 W       |            |
| Mains frequency                                  | 50/60 Hz      |            |
| Edging height                                    | 18–65 mm*     |            |
| Edge thickness                                   | 0.5–3.0 mm*   |            |
| Inner radius                                     | > 50 mm*      |            |
| Heating time                                     | approx. 8 min |            |
| Melting temperature                              | Setting 1     | 190° C     |
| Default setting                                  | Setting 2     | 200° C     |
| Melting temperature                              | Setting 1/2   | 100–210° C |
| Setting range                                    |               |            |
| Feed speed                                       | 1st gear      | 2 m/min    |
|  | 2nd gear      | 4 m/min    |
| Safety class                                     | 1             |            |
| Weight (without glue cartridges and mains cable) | 7.9 kg        |            |

\* Depending on material

### **CONTURO** Items included

|  | Order no.     |
|--|---------------|
| <b>Edge bander KA 65 Plus</b><br>Edge banding machine, complete with guide table, 4x natural EVA adhesive, in a SYSTAINER SYS 4 T-LOC  | <b>574610</b> |
| <b>Edge bander KA 65 Set</b><br>same as KA 65 Plus with edge trimming set SYS KB-KA 65, in a SYSTAINER SYS 4 T-LOC   | <b>574617</b> |
| <b>Edge trimming set SYS KB-KA 65</b><br>Edging holder, additional roller, trimming machine, scraper, base runner scratch protector with 3x felt pad, 5x polishing felt, 20x abrasive sheets StickFix Brilliant 2 80x133 mm P320, hand sanding block 80x133 mm, 5x StickFix sanding cloth S 800, polish MPA 6000 | <b>500177</b> |



## The CONTURO. **For the perfect edge.**

Edging straight surfaces, curves, radii, convex and concave shapes as well as internal corners is easy with the CONTURO. Edging can even be attached to mitred edges to an outstanding quality with the stationary unit. Quick, easy and clean – ideal for shaped parts and small batches.

Suitable for machining all types of wood, plastic or melamine edging with a height of 18–65 mm and edge thickness of 0.5–3.0 mm (depending on material). The CONTURO is packed away safely in a SYSTAINER, extremely mobile and delivers a perfect edge quality, even in combination with system accessories.

# FESTOOL

Tools for the toughest demands

## Festool Australia

PO Box 4401

Dandenong South VIC 3164

Phone: 1300 063 900

Email: [customercare@tooltechnic.com.au](mailto:customercare@tooltechnic.com.au)



Service all-inclusive: 3-year extended warranty, Repair service, 10-year spare parts availability, application advice for customers, customer hotline 1300 063 900. Visit [www.festool.com.au](http://www.festool.com.au) for details



Dealer

**Festool CONTURO**

Valid from 2014

**Order no. 63514**

Subject to alterations and errors. Products may differ from those pictured.

Created for Festool Group GmbH & Co. KG, 73240 Wendlingen, 1/2014

[www.festool.com.au](http://www.festool.com.au)